

GLASS FEEDER OPERATED WITH OXY-GAS COMBUSTIONField of the Invention

5       **[0001]**       The present invention relates to the production of glass and particularly to improvements in glass feeders.

Background of the Invention

10       **[0002]**       A glass feeder is the piece of equipment that is used in the glass industry to transport molten glass from the melting furnace, in which the glassmaking materials (soda ash, silica, scrap, and the like) are melted to form the molten glass, to the forming machines in which the desired glass articles  
15       are formed from the molten glass. The fundamental function of this equipment, besides providing a route for the molten glass between the furnace and the forming machines, is conditioning the molten glass, that is, permitting it to take on the appropriate  
20       desired viscosity, temperature and mass flow uniformity by the time it reaches the forming machines.

25       **[0003]**       There are a large variety of glass feeders according to size, quantity, and furnace characteristics. The size normally depends on the pull rate (i.e. the rate of production of molten glass) and the type of glass produced. Furnaces equipped with one to five glass feeders are normally found in the industry. Their length ranges from 3 to 15 meters and the width from 0.4 to 1.5m.

30       **[0004]**       The glass enters the glass feeder in a molten state and must be kept in the molten state as it passes through the feeder. The heat is generally

provided by either electric means or fuel combustion. The majority of glass feeders are heated by combustion of air and fuel gas, such as natural gas, LPG (liquefied petroleum gas) or others. In conventional practice, to provide uniform heating several small pre-mixed fuel-gas burners, firing with air at ambient temperature, are installed in the sidewalls of the glass feeder, projecting (and projecting a flame) orthogonally to the direction of glass flow.

10       **[0005]**       To condition the glass, molten glass at a temperature on the order of around 1300°C leaving the furnace enters the glass feeder, and among other things the temperature of the molten glass is reduced in as uniform a way as possible, delivering homogeneous glass to the forming machines.

15       **[0006]**       To reduce the molten glass temperature, cooling air can be injected into the center of the glass feeder. This reduces the temperature where the glass flow is hotter and has the highest velocity, while fuel gas is fired in the orthogonally oriented burners in both side walls where glass velocity tends to be lower and glass tends to be cooler due to heat losses at or through the walls.

20       **[0007]**       The firing and heating by combustion with air provides very low flame emissivity. The burner blocks and feeder roof are designed and built in a way that the heat delivered to these regions is in part directed back to the molten glass, near the side wall, to improve the heating where heat is required.

30       **[0008]**       In addition to inefficient and non-uniform heat transfer, the conventional system has

other limitations. The turn down ratio is limited, and possibilities exist of flash back when working with low gas velocities and of flame blow off when working with high velocities.

5           **[0009]**     Prior art attempts to solve these problems have used premixed air-gas burners, installed along the feeder side walls, which produce very short and hot flames. The axes of these burners are orthogonal to the flow direction of the molten glass  
10           and are located in a horizontal plane just above the molten glass surface.

**[0010]**     These flames release high heat fluxes over the glass surface near the side walls as an attempt to gather higher flame temperatures in these  
15           regions. This lowers the shear stresses in these zones of glass flow responsible for defects in the end product.

**[0011]**     Other attempts to improve glass feeder performance have been in new burner block and roof  
20           designs, to improve heat transfer to the glass closer near the side walls.

**[0012]**     Thus, there remains an unmet need for techniques that achieve better, more uniform temperature distribution along cross sections of a  
25           molten glass feeder, so that the glass temperatures close to the side walls of the feeder are as equal as possible compared with those in the middle of the glass flow, for all horizontal axes in the same cross section, so as to provide better temperature  
30           performance of the forming machines and better quality in the end-products.

BRIEF SUMMARY OF THE INVENTION

[0013] One aspect of the present invention is a glass feeder comprising

- 5 (A) a floor, a pair of opposed side walls, a pair of opposed end walls, and a roof, which together define an enclosed chamber, inlet means in one end wall for receiving molten glass into the chamber, and outlet means in the other end wall or floor for discharging molten glass from the chamber,
- 10 (B) at least one burner passing through each side wall, through a burner block, into the chamber, each burner comprising first and second burner head means for combusting oxidant and fuel within said chamber, means for feeding fuel from outside the chamber through
- 15 a first set of one or more openings in each of said first and second burner head means from within said burner head means into the chamber, and means for feeding oxidant from outside the chamber through a second set of one or more openings in each of said
- 20 first and second burner head means from within said burner head means into the chamber so that said fuel and oxidant mix at said burner head means after passing therethrough and do not mix before passing therethrough,
- 25 wherein said first and second burner head means are oriented with respect to each other that combustion of fuel and oxidant fed therethrough produces flames at each burner head which extend in axially opposite directions and are oriented such that said flames
- 30 extend parallel to the side wall through which the burner passes and adjacent to said side wall and to the glass surface.

[0014] Another aspect of the present invention is a method for operating a glass feeder, comprising flowing molten glass through a glass feeder having a floor, opposing side walls, opposing end walls and a roof which together define a chamber through which the molten glass flows, providing at least one burner passing through each side wall through a burner block into the chamber, each burner comprising first and second burner head means for combusting oxidant and fuel within said chamber, means for feeding fuel from outside the chamber through a first set of one or more openings in each of said first and second burner head means from within said burner head means into the chamber, and means for feeding oxidant from outside the chamber through a second set of one or more openings in each of said first and second burner head means from within said burner head means into the chamber so that said fuel and oxidant mix at said burner head means after passing therethrough and do not mix before passing therethrough,

wherein said first and second burner head means are oriented with respect to each other that combustion of fuel and oxidant fed therethrough produces flames at each burner head which extend in axially opposite directions, and wherein each burner is oriented such that said flames extend parallel to the side wall through which the burner passes and adjacent to said side wall and to the glass surface,

combusting fuel and oxidant at said burners to produce flames which extend along both side walls at the molten glass surface.

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] Figure 1 depicts a glass feeder embodying the present invention.

5 [0016] Figure 2 is a partial cross-sectional top view of a burner incorporating the present invention.

[0017] Figure 3 is a plan view of the burner of Figure 2, seen from one side.

10 [0018] Figure 4 is a cross-sectional top view of the burner of Figure 2.

[0019] Figure 5 is a view of a burner block useful in this invention.

15 [0020] Figure 6 is a plan view of an additional refractory block useful in this invention.

DETAILED DESCRIPTION OF THE INVENTION

[0021] Referring first to Figure 1, a glass feeder incorporating the present invention is represented. The feeder 1 includes opposing side walls 2 and 3, opposing end walls 4 and 5, a floor (not shown), and a roof 6 which is shown in phantom. The walls, floor and roof together define a chamber. Molten glass 10 enters the chamber through inlet 7 in end wall 4, flows under the influence of gravity through the chamber in the direction of the arrow, and leaves the chamber via outlet 8 in end wall 5 or floor. Any means useful to provide molten glass into inlet 7, and any means useful to form products or otherwise to act on molten glass exiting outlet 8, can be used in association with feeder 1.

[0022] The floor, walls and roof are made of any material capable of retaining its physical

integrity when exposed to the conditions of very high temperature and highly alkaline atmosphere which prevail within the chamber during operation. Any conventional refractory material can be used. Many  
5 examples of refractory material that would be useful for this use are known to those familiar with this field. Examples of useful refractory material include structural refractories such as fused, cast and agglomerated refractories (such as AZS, alumina,  
10 zirconia, chromite, high alumina, and the like), and insulation refractories (such as calcium silicate, silicon-alumina, alumina, and the like).

[0023] Figure 1 also depicts burner 11, described in more detail below. Burner 11 extends  
15 through the wall 2 and includes within the chamber a pair of burner heads which produce flames 12 and 13 that extend in axially opposite directions close to side wall 2 and close to the top surface of the molten glass 10. By "axially opposite directions" is meant  
20 that the axes of the two flames are coaxial (i.e. the same axis, which is preferred) or are parallel to each other.

[0024] The flames are adjacent to the side wall and to the glass surface. Preferably the distance  
25 between the flame axis and the glass surface, in the vertical plane, is from 40 to 90 mm. In the horizontal plane, the distance between the flame axis and the adjacent wall is from 0 to 70 mm.

[0025] Burner 11 is fed fuel and oxidant from  
30 fuel source 14 and oxidant source 15 which are both outside the chamber. A corresponding burner through side wall 3 is shown as well. It can be fed from its

own separate sources of fuel and oxidant, or from the same sources that feed burner 11.

[0026] Each side wall should contain at least one such burner. Depending on the size of the glass  
5 feeder chamber and the size of the burners, two or more such burners can be provided in each side wall. Preferably, they would be arranged so that flame tips from adjacent burner heads do not overlap.

[0027] Preferably, each burner and its  
10 respective burner block requires only one opening passing through the side wall, for all associated feed lines and any associated structure for holding the burner heads within the chamber. A useful way to achieve these objectives is to provide concentric  
15 conduits for feeding the fuel and oxidant, with the larger of the two conduits being also the structure that supports the burner heads within the chamber. Preferably, the outer of the two concentric conduits carries the oxidant and the inner conduit carries the  
20 fuel, to lessen the risk of the fuel degrading or polymerizing within its conduit upon exposure of the fuel conduit to the hot conditions within the chamber. The conduits should be made of material that can withstand the temperature conditions within the  
25 chamber, preferably of high-temperature alloys such as Haynes 188, Hastelloy, or Inconel. The conduits can optionally be encased in refractory material to assemble it in the burner block.

[0028] Suitable fuels include gaseous  
30 combustible hydrocarbonaceous products such as natural gas, methane, LPG (liquefied petroleum gas), propane, and mixtures thereof and the like.



[0029] Suitable oxidants include gaseous streams and mixtures comprising at least 20.9 vol.% oxygen, i.e. having at least the oxygen content of air. Preferably the oxygen content is at least 90 vol.% oxygen, and more preferably at least 99 vol.% oxygen. Commercial oxygen can be used, or oxygen-enriched air.

[0030] A preferred embodiment of the burner is depicted in Figures 2, 3 and 4. Figure 2 is a top view of the burner 11 of Figure 1, in which part of the burner 11 and parts of conduits 23 and 26 have been cut away. Burner 11 contains burner heads 21 and 22 which lie on the same axis but face away from each other. Feed conduit 20 is what passes through a suitably dimensioned opening in the burner block in which both are assembled in a side wall of the feeder. Within feed conduit 20, fuel conduit 23 is concentrically disposed within oxidant conduit 26 and they both extend through wall 2, inside the burner block, from outside the chamber. Fuel conduit 23 divides into branches 24 and 25. Branch 24 conveys fuel to burner head 21, and branch 25 conveys fuel to burner head 22. Fuel conduit 23 and branches 24 and 25 convey fuel only to one or more orifices in burner heads 21 and 22 by which fuel leaving the conduits can pass only through the orifices into the chamber of the glass feeder.

[0031] Oxidant conduit 26 conveys oxidant to the area within burner 11 outside fuel conduit 23 and branches 24 and 25. Burner 11 encloses the end of oxidant conduit 26 so that oxidant can leave burner 11 only through orifices in burner heads 21 and 22. In this way, fuel and oxidant do not mix at all within

burner 11 or upstream therefrom, and do mix only outside the burner heads (and thus within the chamber) so that they can combust.

[0032] In preferred examples of furnaces  
5 embodying this invention the distance between the flame axis and the molten glass surface, in the vertical plane, is 47 mm. In the horizontal plane, the distance between the flame axis and the adjacent wall is 11 mm.

[0033] It will be recognized that other  
10 arrangements of the feed lines and burner heads are possible, so long as mixing of fuel and oxidant within the burner 11 is avoided.

[0034] Figure 3 depicts an embodiment of the  
burner head 21, seen in a view looking directly at the  
15 face of burner head 21. Orifice 31, preferably situated at or near the center of burner head 21, is the end of branch 24 that carried fuel to and through burner 11. In operation, fuel emerges from orifice 31. Of course, there can be more than one orifice for fuel to pass  
20 through, so long as all such orifices are connected to the fuel conduits without permitting mixing of fuel and oxidant within the burner 11.

[0035] Burner head 21 is also provided with one  
or more orifices 32 and 33 which communicate with the  
25 oxidant being fed into burner 11. The one or more orifices passing fuel through the burner head, and the one or more orifices passing oxidant through the burner head, should be located with respect to each other that fuel and oxidant mix, thereby enabling combustion to  
30 occur within the chamber outside the burner head.

[0036] The embodiment shown in Figures 3 and 4 is a particularly preferred mode of the invention. The

two sets of holes 32 and 33 are arranged respectively in two different radii from the fuel orifice 31. The orifices 32, which are on the side of the burner head that is closer to the center of the chamber, have  
5 smaller diameters than orifices 33 which are on the side that is closer to the wall. Also, as can be seen in Figure 4, the axes of orifices 33 (and of orifices 33' in burner head 22) are parallel to the axis of the fuel orifice, whereas the axes of orifices 32 (and of  
10 orifices 32' in burner head 22) are convergent to the axis of orifice 31. This configuration compels the flames to develop over a long distance parallel to and very close to the wall surface. The flames thus produced are narrow brush-type.

15       **[0037]**       The burners can be made by manufacturing separately the feed line containing conduits 23 and 26, and each burner head, and then assembling the parts into the completed burner.

20       **[0038]**       The burners of the present invention are inserted through burner blocks through the side walls without deviation from the conventional vertical aspect of the side wall. Optionally the burner can be assembled into the burner block with an additional refractory material to better protect the burner parts  
25 from overheating. One example of burner block is shown as 51 in Figure 5. The burner 11 of Figures 2-4 is internally assembled in this refractory material, with the conduit 20 lying in passage 53 and the faces of burner heads 21 and 22 facing out of the open ends of  
30 hole 52.

**[0039]**       The burners of the present invention can be installed together with additional refractory

blocks. One example of such additional refractory block is shown as 61 in Figure 6. Enough blocks 61 are used side by side so that the total length of the projection 62 extend as far as the length of the flames.

5 Projection 62 extends into the furnace the same distance from the side wall as the width of the flame. Thus, projection 62 reflects heat toward the molten glass surface that would otherwise rise from the flame away from the molten glass surface.

10 [0040] The present invention is also useful in retrofitting of existing glass feeders. That is, the burners and burner blocks already in place in a glass feeder are removed and replaced by the burners and burner blocks described herein. Because the flames  
15 from the burners described herein extend along the length of the side wall rather than orthogonally into the chamber, one of the burners described herein can replace several, perhaps 3 to 8, of the conventional orthogonally oriented burners.

20 [0041] The present invention affords numerous significant advantages. The flames produced by the oxygen-gas reaction are long, hard, much hotter and luminous. This allows higher radiant heat fluxes over  
25 the molten glass surface in very close proximity to the internal surface of the side walls. This allows higher temperatures in these regions, which improves the overall operation and glass flow of the feeder. Much better uniformity of temperature across the molten  
30 glass from side to side of the chamber is realized, which leads directly to improved flow characteristics of the molten glass. Fewer burners are needed for a



[0042] In addition, the fuel gas consumption, for the same mean cross section temperature, is generally on the order of only 60% of the original consumption, compensating for the additional cost of the oxygen.

10       **[0043]**       Another advantage of this system is that less off-gases are generated that would need to be captured, recycled, or disposed of.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041 1042 1043 1044 1045 1046 1047 1048 1049 1050 1051 1052 1053 1054 1055 1056 1057 1058 1059 1060 1061 1062 1063 1064 1065 1066 1067 1068 1069 1070 1071 1072 1073 1074 1075 1076 1077 1078 1079 1080 1081 1082 1083 1084 1085 1086 1087 1088 1089 1090 1091 1092 1093 1094 1095 1096 1097 1